

FOUNDED 1865  
MANUFACTURER OF REFRIGERATION  
TECHNOLOGY FOR THE HEALTH SECTOR

**Philipp Kirsch GmbH**

Okenstraße 103  
D-77652 OFFENBURG-GERMANY  
www.kirsch-medical.com

## FROSTER-BL-180



Digital temperature display

Minimum/maximum  
temperature memory

Key switch

Visual and audible alarm  
signal, even in the case of  
power failure

Forced-air cooling

Comfortable access

3 drawers with cover plate

Automatic fast defrosting

Connection for forwarding  
alarms and for PC-sup-  
ported temperature docu-  
mentation

Condensate evaporation



### The KIRSCH-PC-KIT

In conjunction with the soft-  
ware KIRSCH DATANET allows  
a consistently documentation,  
including real-time monitoring  
of your refrigerators and free-  
zers from the PC.



### Storage temperature -41 °C

The powerful cooling machine  
keeps the temperature safe at  
-41 °C.



**EXCLUSIVE DISTRIBUTOR (Sole Agent)**  
**PT. PRIMA ALKESINDO NUSANTARA**  
Kompleks Perkantoran Gading Bukit Indah Blok C No. 12-15,  
Jl. Bukit Gading Raya, Kelapa Gading Permai, Jakarta 14240  
Telp. : (021) 4513875 Fax. : (021) 4513876  
E-mail : corporate@prima-alkesindo.com  
Website : www.prima-alkesindo.com

# FROSTER BL 180



according to DIN 58375

## ■ PRO-ACTIVE- Control:

Permanent, proactive monitoring of the performance data and alerts in the case of deviations – so that you can take countermeasures in good time before a fault threatens your chilled goods; world's most accurate temperature control in refrigerated areas thanks to two standard PT-1000 sensors

- **External housing** made from galvanised sheet steel (rust-proof), with white, anti-scratch powder coating. Length of the plug cable: approx. 2.8 m.
- **Adjustable feet** to compensate for uneven floors.
- **Interior made** from smooth aluminium with colourless protective coating.
- **Interior consists** of three drawers of stainless steel with stops, with cover plate on telescopic runners. Capacity per drawer app.
- **Extra-thick 70-mm insulation**, made from high-quality, compression-moulded and environmentally friendly material. Energy saving.
- **Self-closing door** with easy-to-replace plastic magnetic seal frame, lockable.
- **Door stop** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.

- **Forced-air cooling**, switches off automatically when you open the door, ensures a uniform temperature and minimizes temperature deviations.
- **Automatic fast defrosting** thanks to time-limited and temperature-monitored reversal of the refrigerant circuit.
- **Condensate evaporates** in stainless steel heated dish beneath the refrigerator floor.
- **Key switch protected control panel against tampering.** Membrane keyboard with digital temperature display and minimum/maximum temperature memory.
- **Warning functions** with visual and audible alarm signal in the case of power failure and temperature deviations. In the case of power failure, the monitoring unit remains in operation for approx. 30 hours on battery power. Door open alarm after 60 seconds.
- **Alarms** can be forwarded using the potential-free contact (e.g., to a mobile phone with optional GSM-Module or to a control centre).
- **Data documentation** can be read via USB interface with KIRSCH Datanet software.
- **Ventilation-enforced refrigerating machine**, vibration free, hermetically sealed, energy saving, low-noise, easy to service. Inlet air and exhaust air flow through the ventilation slits at the front.

## Specification

Capacity	170 litres
Temperature setting	-41 °C
Voltage	220 – 240 V, 50 Hz
Power consumption	453 watts
Normal consumption	6.54 kWh/24 h
Admissible ambient temperature	from +10 °C to +32 °C
Heat emission (max.)	489 watts
Exterior dimensions (including door handle and distance from wall)	w x d x h = 70 x 77 x 122 cm
Interior dimensions	w x d x h = 55 x 52 x 60 cm (usable width 3 cm, usable depth 15 cm, usable height 13 cm less)
Exterior dimensions with door open at 90°	w x d = 70 x 136 cm
Drawer inner dimensions	w x d x h = 52 x 32 x 10 cm
Max. load drawer	50 kg
Weight	Net weight 100 kg, gross weight 110 kg

## Optional equipment

- **Equipped with castors.**
- **Drawer insert** (set) with 3 adjustable length and 21 cross dividers per drawer.
- **Additional length and cross dividers.**
- **GSM-Module** for alarm text message transmission.
- **Temperature documentation:**
  - PC-KIT-NET.
  - 4-pin PT 100 or PT 1000 temperature sensor, class 1/3 B, including built-in reference body.
  - Disc-type pen recording thermometer, with 7-day measuring cycle, incorporated, with 100 recording discs and 5 felt tip pens.