

FOUNDED 1865
MANUFACTURER OF REFRIGERATION
TECHNOLOGY FOR THE HEALTH SECTOR

Philipp Kirsch GmbH

Okenstraße 103
D-77652 OFFENBURG-GERMANY
www.kirsch-medical.com

MED-520



Digital temperature display

Antifreeze

Key switch

Forced-air cooling

Minimum/maximum
temperature memory

Visual and audible alarm
signal, even in the case of
power failure


Comfortable access

Connection for
forwarding alarms and for
PC-supported temperature
documentation

12 drawers


Automatic defrosting

Condensate evaporation



Fast defrosting

Fast defrosting significantly
reduces defrosting periods
with minimal temperature
variations.



Upper drawer lockable

The upper drawer can be
locked by default.



EXCLUSIVE DISTRIBUTOR (Sole Agent)
PT. PRIMA ALKESINDO NUSANTARA
Kompleks Perkantoran Gading Bukit Indah Blok C No. 12-15,
Jl. Bukit Gading Raya, Kelapa Gading Permai, Jakarta 14240
Telp. : (021) 4513875 Fax. : (021) 4513876
E-mail : corporate@prima-alkesindo.com
Website : www.prima-alkesindo.com

MED 520

PRO-ACTIVE



according to DIN 13277

- **PRO-ACTIVE-Control:** Permanent, proactive monitoring of the performance data and alerts in the case of deviations – so that you can take countermeasures in good time before a fault threatens your chilled goods; world's most accurate temperature control in refrigerated areas thanks to two standard PT-1000 sensors.
- **External housing** made from galvanised sheet steel (rustproof), with white, anti-scratch powder coating. Length of the plug cable: approx. 3 m.
- **Equipped with castors.**
- **Adjustable feet** to compensate uneven floors.
- **Interior** made from smooth aluminium with colourless protective coating. Gibs (every 15 mm) for flexible interior arrangement.
- **Interior consists** of twelve black drawers with stops, on roller runners. There are two adjustable length dividers and twelve adjustable cross dividers per drawer. Storage surface per drawer = 0.23 m².
- **Extra-thick 70-mm insulation**, made from high-quality, compression-moulded and environmentally friendly material. Energy saving.
- **Self-Closing-Door** with easy-to-replace plastic magnetic seal frame, lockable.
- **Door hinge** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.
- **Forced-air cooling**, switches off automatically when you open the door, ensures a uniform temperature and minimizes temperature deviations.
- **Automatic fast defrosting** thanks to time-limited and temperature-monitored reversal of the refrigerant circuit.
- **Condensate evaporation** in stainless steel heated dish beneath the refrigerator floor.
- **Key switch** protected control panel against tampering. Membrane keyboard with digital temperature display and minimum/maximum temperature memory.
- **Data documentation** can be read via USB interface with KIRSCH Datanet software
- **Warning functions** with visual and audible alarm signal in the case of temperature deviations and power failure. In the case of power failure, the monitoring unit remains in operation for approx. 30 hours on battery power.
- **Alarms** can be forwarded using the potential-free contact (e.g., to a mobile phone with optional GSM-Module or to a control centre).
- **Antifreeze** against sub-zero temperatures.
- **Ventilation-enforced refrigerating machine**, hermetically sealed, energy saving, low noise, easy to service.

Specification

| | |
|--|---|
| Capacity | 500 litres |
| Temperature setting | approx. +2 °C to +15 °C |
| Voltage | 220 – 240 V, 50 Hz |
| Power consumption | 260 watts |
| Normal consumption | 1.50 kWh/24 h |
| Admissible ambient temperature | from +10 °C to +38 °C |
| Heat emission (max.) | 560 watts |
| Exterior dimensions (including door handle and distance from wall) | w x d x h = 77 x 76 x 195.5 cm |
| Interior dimensions | w x d x h = 60 x 57 x 140 cm (usable depth 10 cm) |
| Exterior dimensions with door open at 90° | w x d = 77 x 144 cm |
| Drawer inner dimensions | w x d x h = 57.3 x 39 x 5.6 cm |
| Max. load drawer | 24 kg |
| Weight | Net weight 145 kg, gross weight 168 kg |

(measured values based on Eccol R600a)

Optional equipment

- **Glass door with lock.**
- **LED-Illumination** mounted on side wall.
- **Adjustable** feet to compensate uneven floors.
- **Top drawer** can be locked.
- **Decorative door frame** for attaching the customer's decorative plates.
- **Additional length and cross dividers.**
- **Shelf** w x d = 59.7 x 45 cm on rails or overlays instead of drawer (max. load: 40 kg).
- **Condensate container** can be emptied manually if no condensation is required (e.g., in an operating theatre).
- **60 Hz cooling machine** upon request
- **Vario Support**, Storage Shelf on roller runners.
- **GSM-Module** for alarm text message transmission (e.g., to a mobile phone).
- **Temperature documentation:**
 - PC-KIT-NET (network capable version)
 - 4-pin PT 100 or PT 1000 temperature sensor, class 1/3 B, including built-in reference body (measurement bottle or refrigerating block).
 - Mechanical pen-recording thermometer with two waxed paper strips.