

FOUNDED 1865  
MANUFACTURER OF REFRIGERATION  
TECHNOLOGY FOR THE HEALTH SECTOR

**Philipp Kirsch GmbH**  
Okenstraße 103  
D-77652 OFFENBURG-GERMANY  
[www.kirsch-medical.com](http://www.kirsch-medical.com)

## LABO-340



#### Display at eye-level

The display is positioned at eye-level to make it easier to read and simplify operation.



#### Optimized air guide plate

The optimized air guide plate reduces temperature deviations inside the system to a minimum.

# LABO 340

## PRO-ACTIVE

330 l /  
460 l

+2 to  
+20 °C

USB



### PRO-ACTIVE- Control:

- Permanent, proactive monitoring of the performance data and alerts in the case of deviations – so that you can take countermeasures in good time before a fault threatens your chilled goods; world's most accurate temperature control in refrigerated areas thanks to two standard PT-1000 sensors.
- External housing** made from galvanised sheet steel (rust-proof), with white, anti-scratch powder coating. Length of the plug cable: approx. 2.8 m.
- Adjustable feet** to compensate uneven floors.
- Interior** made from smooth aluminium with colourless protective coating. Gibs (every 15 mm) for flexible interior arrangement.
- Interior** of LABO 340 PRO-ACTIVE consists of one black drawer and four plastic-coated shelves on overlays. Interior of LABO 468 PRO-ACTIVE consists of four plastic-coated shelves on overlays.
- Extra-thick 55 mm energy saving insulation**, made from high-quality, compression-moulded and environmentally friendly material.
- Self-closing door** with easy-to-replace plastic magnetic seal frame, lockable.
- Door hinge** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.

- Forced-air cooling**, switches off automatically when you open the door, ensures a uniform temperature and minimizes temperature deviation.
- Automatic defrosting** with time limit and temperature monitoring.
- Condensate evaporates** in the refrigerating machine interior.
- Key switch** protected control panel against tampering. Membrane keyboard with digital temperature display and minimum/maximum temperature memory.
- Warning functions** with visual and audible alarm signal in the case of temperature deviations or other malfunctions. Door open alarm after 60 seconds.
- Alarms** can be forwarded using a potential-free contact (e.g., to a mobile phone with optional GSM-Module or to a control centre).
- Power failure alarm** (visual and audible alarm), the monitoring unit remains in operation for approx. 30 hours on battery power.
- Data documentation** can be read via USB interface with KIRSCH Datanet software.
- Antifreeze** against sub-zero temperatures.
- Statically ventilated** (LABO 340 PRO-ACTIVE) or **ventilation-enforced** (LABO 468 PRO-ACTIVE) refrigerating machine, hermetically sealed, energy saving, low-noise, easy to service.

## Specification

### LABO 340 PRO-ACTIVE

Capacity	330 litres
Temperature setting	approx. +0 °C to +15°C
Voltage	220 – 240 V, 50/60 Hz
Power consumption	110 watts
Normal consumption	0.65 kWh/24 h
Admissible ambient temperature	from +10 °C to +38 °C
Heat emission (max.)	166 watts
Exterior dimensions (including door handle and distance from wall)	w x d x h = 67 x 66 x 189 cm
Interior dimensions	w x d x h =* 53 x 45 x 128 cm
Exterior dimensions with door open at 90°	w x d = 67 x 124 cm
Shelf size	w x d = 52,7 x 39 cm
Drawer inner dimensions	w x d x h = 50,4 x 32 x 5.6 cm
Max. load drawer/ shelf	16 kg/40 kg
Weight	Net weight 90 kg, gross weight 104 kg

\*usable depth 5 cm less.

## Optional equipment

- Glass door** with lock.
- LED-Illumination** mounted on side wall.
- Decorative door frame** for attaching the customer's decorative plates.
- Door fitting.**
- Equipped with castors.**
- Condensate container** can be emptied manually if no condensation is required (e.g., in an operating theatre).
- Plastic drawer on roller runners**
- Additional length and cross dividers.**
- Additional shelf** on rails or overlays.
- Basket** on rails (only for LABO 468 PRO-ACTIVE) w x d x h = 60 x 45 x 10 cm.
- Aluminium tray** with rails (only for LABO 468 PRO-ACTIVE) w x d x h = 60 x 40 x 2.5 cm.
- Vario Support**, Storage Shelf on roller runners.
- GSM-Module** for alarm text message transmission.
- Temperature documentation:**
  - PC-KIT-NET (network capable version)
  - 4-pin PT 100 or PT 1000 temperature sensor, class 1/3 B, including built-in reference body (measurement bottle or refrigerating block).
  - Mechanical pen-recording thermometer with two waxed paper strips.