



Total blood Bank Processing Solution

PLATELET INCUBATOR

PRESVAC incubators offer advance security for your platelets products.

- Platelet incubator at controlled temperature
- Digital temperature indicator.
- Programmable temperature between 18° C and 22° C.
- Forced air circulation maintains an homogeneous temperature all inside the equipment.
- Audible and visual high/low programmable alarms.
- Tempered glass door.
- Non CFC, commercially available refrigerant.
- Key lock.
- Stainless steel interior cabinet.



OPTIONAL :

- Chart recorder.
- Door ajar alarm.
- Power failure alarm.
- Remote alarms.



TECHNICAL FEATURES

MODEL	AP-48 LT
DOOR	SINGLE TEMPERED GLASS
INTERIOR	STAINLESS STEEL
ELECTRICAL	115 V 60 Hz 9 FLA 230 V 50/60 Hz 5,2 FLA
EXTERIOR DIMENSIONS (cm)	65 x 63 x 85
AGITATOR CAPACITIES	AP-48 L



EXCLUSIVE DISTRIBUTOR (Sole Agent):
PT. PRIMA ALKESINDO NUSANTARA
Gading Bukit Indah, Jl. Bukit Gading Raya Blok C 12-15
Kelapa Gading Permai - Jakarta 14240
Telp. : (021) 4513875 Fax. : (021) 4513876
E-mail : corporate@prima-alkesindo.com
Website : www.prima-alkesindo.com