

FOUNDED 1865  
MANUFACTURER OF REFRIGERATION  
TECHNOLOGY FOR THE HEALTH SECTOR

**Philipp Kirsch GmbH**

Okenstraße 103  
D-77652 OFFENBURG-GERMANY  
www.kirsch-medical.com

## FROSTER-MED-95



1 drawer and 2 shelves

Minimum/maximum  
temperature memory

Standalone or undercounter  
installation

Connection for forwarding  
alarms and for PC-supported  
temperature documentation

Rapid freezing cycle

Visual and  
acoustic alarm signal

Key switch

Digital temperature display



See [www.kirsch-medical.com](http://www.kirsch-medical.com) for  
the installation drawing.



### Easy-to-clean ventilation slits

Large, smooth lamellas for  
easy cleaning of the ventilation  
slits.



### Power package

High-performance freezer for  
standalone or undercounter  
installation (up to -25 °C).



EXCLUSIVE DISTRIBUTOR (Sole Agent)

**PT. PRIMA ALKESINDO NUSANTARA**

Kompleks Perkantoran Gading Bukit Indah Blok C No. 12-15,

Jl. Bukit Gading Raya, Kelapa Gading Permai, Jakarta 14240

Telp. : (021) 4513875 Fax. : (021) 4513876

E-mail : [corporate@prima-alkesindo.com](mailto:corporate@prima-alkesindo.com)

Website : [www.prima-alkesindo.com](http://www.prima-alkesindo.com)

# FROSTER MED 95



- **PRO-ACTIVE-Control:** Permanent, proactive monitoring of the performance data and alerts in the case of deviations – so that you can take countermeasures in good time before a fault threatens your chilled goods; world’s most accurate temperature control in refrigerated areas thanks to two standard PT-1000 sensors
- **External housing** made from galvanised sheet steel (rustproof), with white, anti-scratch powder coating. Length of the plug cable: approx. 2.8 m.
- **Adjustable feet** positioned at the front to compensate uneven floors.
- **Interior** made from impact-resistant, white plastic with moulded-in shelves.
- **Interior consists** of one drawer with stop and two plastic-coated shelves. There is one adjustable length divider and six adjustable cross dividers per drawer. Storage surface per drawer = 0.13 m<sup>2</sup>.
- **Extra-thick 50-mm insulation**, made from high-quality, compression-moulded and environmentally friendly material. Energy saving.
- **Door** with easy-to-replace plastic magnetic seal frame, lockable.

- **Door hinge** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.
- **Manual defrosting.** Removable condensation container.
- **Key switch** protected control panel against tampering. Membrane keyboard with digital temperature display and minimum/maximum temperature memory.
- **Warning functions** with visual and audible alarm signal in the case of temperature deviations and power failure.
- **Alarms** can be forwarded using a potential-free contact (e.g., to a mobile phone with optional GSM-Module or to a control centre).
- **Data documentation** can be read via USB interface with KIRSCH Datanet software.
- **Rapid freezing cycle** ensures that the goods to be cooled are frozen quickly.
- **Ventilation-enforced refrigerating machine**, hermetically sealed, energy saving, low noise, easy to service. Inlet air and exhaust air flow through the ventilation slits at the front.
- **Low-noise compressor** reduces noise to 40 dB (corresponds to noise level I; sound perception: whisper).

## Specification

Capacity	95 litres
Temperature setting	approx. -5 °C to -25 °C
Voltage	220 – 240 V, 50 Hz
Power consumption	123 watts
Normal consumption	1,33 kWh/24 h
Admissible ambient temperature	from +10 °C to +32 °C
Heat emission (max.)	162 watts
Exterior dimensions (including distance from wall)	w x d x h = 54 x 53.5 x 82 cm
Interior dimensions	w x d x h = 44 x 42 x 47 cm (usable depth 5 cm, usable width 2 cm less)
Exterior dimensions with door open at 90°	w x d = 54 x 105.5 cm
Shelf size	43 x 36 cm
Drawer inner dimensions	w x d x h = 40 x 32 x 5.6 cm
Max. load drawer/shelf	13 kg/25 kg
Weight	Net weight 50 kg, gross weight 54 kg

(measured values based on Eccol R600a)

## Optional equipment

- **Tabletop** (exterior dimensions: 85 cm in height).
- **Decorative door frame** for attaching the customer’s decorative plates.
- **Door fitting.**
- **Equipped with castors.**
- **Additional drawer or shelf.**
- **Additional length and cross dividers.**
- **Alarm** is also triggered in the case of power failure (visual and audible alarm); the monitoring unit remains in operation for approx. 30 hours on battery power.
- **GSM-Module** for alarm text message transmission (e.g., to a mobile phone).
- **Temperature documentation:**
  - PC-KIT-NET (network capable version)
  - 4-pin PT 100 or PT 1000 temperature sensor, class 1/3 B, including built-in reference body (measurement bottle or refrigerating block).
  - Mechanical pen-recording thermometer with two waxed paper strips.
- **60 Hz cooling machine** upon request