

GEL CARD CENTRIFUGE

CAT. NO.: JKS

Key Benefits:



Robust Design

BLDC motor provides incredibly long life time. Unbreakable rotor and unbreakable cover designed for your safety.



Easy to Use

Only push the start button. Never needs recalibration thanks to integrated sensors. Optional balance sensor available.



Results

Only in 10 minutes your cards are ready to read.



Cost Effective

Low startup cost for small to medium labs who require a centrifuge for their Gel Cards. ODAK Diagnostics also supply gel cards at a competitive price.



Incubator and Reader also available!



www.islab.com.tr



DISCOVER MORE

TECHNICAL SPECIFICATIONS

DESCRIPTION	SPECIFICATION
Power Supply:	220 V / 50 – 60 Hz
Power requirement:	130 W
Max. Load:	24 Gel Card
Display:	LCD Screen
Time Settings:	Could be changed(Precalibrated for ODAK Gel Cards).
RPM Settings:	Could be changed(Precalibrated for ODAK Gel Cards).
Ambient temperature:	2 °C – 35 °C
Alarm/Buzzer:	Yes
Max. relative humidity:	75 %
Opening the lid:	Manual
Dimensions:	Height: 165 mm / Depth: 230 mm / Width: 560 mm
Weight (with cover box):	21 kg

